



Ladies and gentlemen, welcome to browse the brochure of "refrigeration unit for trailer", which R&D by Kingtec. Please feel free to contact our company if we can be of any assistance. Thank you!
We always do our best to serve you.



KINGTEC

Refrigeration unit for trailer



KINGTEC GROUP USA INC
Address: 1165 E Acacia Court Unit A, Ontario CA 91761
Tel: 1 (909) 930-1734 / 1 (909) 930-1763
Toll free: 1 (855) 308-8889
Fax: 1 (650) 472-8091
www.kingtecusa.com

China Production Base
Address: No.1, Rexking Rd. Pearl Development Zone
Heyuan Guangdong China
Tel: +86-762-2286018
Fax: +86-762-3831889
www.kingtec.com.cn



KINGTEC GROUP USA INC
Is a professional manufacturer of refrigeration unit for trailer.

Edition 2014



Refrigeration unit for trailer



TC10/20A-G
REFRIGERATION UNIT FOR TRAILER

TC10A-G / TC20A-G Product Benefits

- Meeting the Needs of Trailer Manufacturers.
- Factory Finished Product.
 - One-Piece-Small Interior Footprint.
 - Easy & Fast Installation.
 - Cost Effective & Long Life & Low Operating Expenses.
 - Light Weight and Compact.
 - 15A 15 amps-Plugs in Anywhere.
 - Easy & Safe Operate.
 - Easy Maintain & Perfect Service.

Product Applications

- Caterers and businesses that are in the hospitality industry.
- Concession trailers that need cold storage.
- Disaster relief and emergency service.
- State and local government need refrigerated trailers .
- Hospitals.
- Restaurants remodeling kitchens or needing temporary or additional cold storage.
- Family reunions.
- Weddings and parties.
- Sporting events with tailgating.
- Hunting trailers.
- Marinas, fish and seafood cold storage and transport.
- Corporate sponsorships, such as marathons, special events that need cold beverages.
- Exhibitions and trade shows that require food and beverage.
- Flower growers and related transportation providers.
- Supermarkets.
- Fast food chains.
- Beverage and food sellers at parks, camp sites and fairs.
- Food processors.



Power inlet.
Temperature controller.
Internal Cargo area Light Switch



Cooling fan of Condenser.



TC20A-G Cold air output Evaporator.
Dual cooling fan



TC10A-G Cold air output Evaporator.
Single cooling fan

Refrigerant R404A CFC-free.

Type	Room Temperature	Room Volume*	Cooling Capacity*	Voltage Consumption	Power	Weight	RLA
TC10A-G	23°F ~41°F (-5°C to +5°C)	283~424 ft ³ (8~12m ³)	4182 BTU	115V / 60Hz / 1Phase	1,11 kW	154 lbs/(70kg)	9.65A
				220V / 50Hz / 1Phase			5A
				230V / 60Hz / 1Phase			4.5A
TC20A-G	23°F ~41°F (-5°C to +5°C)	530~706 ft ³ (15~20m ³)	7412 BTU	115V / 60Hz / 1Phase	1,55kW	187 lbs/(85kg)	13.5A
				220V / 50Hz / 1Phase			7.0A
				230V / 60Hz / 1Phase			6.7A

Ambient temperature 95°F, storage temperature 32°F. (35 degree C to 0 degree C)